



## 1. IDENTIFICATION OF THE MATERIAL AND THE MANUFACTURER

<b>Product Name</b>	<b>MAC BRAKE CLEANER</b>		
	All formats: 500ML AEROSOL		
<b>Statement of Hazard Nature</b>	Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances, New Organisms legislation. Classified as a Dangerous Good for transport purposes.		
<b>Proper Shipping Name</b>	<b>AEROSOLS</b>		
<b>Supplier Name</b>	Arandee Ltd		
<b>Address</b>	108 Rockfield Road, Penrose, Auckland 1061, New Zealand		
<b>Telephone</b>	+64 (9) 579 5139		
<b>Emergency</b>	National Poisons Centre -24 hours	Australia	13 11 26
		New Zealand	0800 POISON 0800 764 766
<b>E-mail</b>	<a href="mailto:sales@arandee.co.nz">sales@arandee.co.nz</a>		
<b>Web Site</b>	<a href="http://www.arandee.co.nz">http://www.arandee.co.nz</a>		
<b>Synonym(s)</b>	MAC Brake Cleaner		
<b>Use(s)</b>	Multi-purpose brake and parts cleaner – cleans without disassembly		
<b>Approval(s)</b>	NA		

## 2. HAZARDS IDENTIFICATION

**AEROSOL - CLASSIFIED AS HAZARDOUS ACCORDING TO CRITERIA IN THE HS (MIN DEG OF HAZ) REGS 2001  
CLASSIFIED AS A DANGEROUS GOOD, UNDER ADG AND NZS 5433**

<b>UN Number</b>	<b>1950</b>		<b>Dangerous Goods Risks</b>
<b>DG Class</b>	<b>2.1.2A</b>	<b>2Y</b>	Contains gas under pressure; may explode if heated Contains refrigerated gas; may cause cryogenic burns or injury.
<b>HAZARD STATEMENTS</b>	H222	223	Flammable aerosols
	H303		May be harmful if swallowed
	H313		May be harmful in contact with skin
	H333		May be harmful if inhaled
	H315		May cause skin irritation
	H319		Causes serious eye irritation
	H336		May cause drowsiness or dizziness
	H373		May cause damage to organs with prolonged or repeated exposure
	H410		Very toxic to aquatic life with long lasting effects
		P210	Keep away from heat/sparks/open flame/hot surfaces
		P211	Do not spray on an open flame, or other ignition source.



---

	P251	Pressurized container. Do not pierce or burn even after use
	P403	Store in a well-ventilated place.
	P410	Protect from direct sunlight
	P412	Do not expose to temperatures exceeding 50°C/122°F
SIGNAL WORD		DANGER

### 3. HAZARDS IDENTIFICATION COMPOSITION OF INGREDIENTS

Ingredient	Formula	Concentration	CAS Number
Ketone		10-60	67-64-1
Aliphatic Hydrocarbon		10-60	64742-49-0
Aromatic Hydrocarbon		10-60	108-88-3
PROPANE	C <sub>3</sub> H <sub>8</sub>	30-60%	74-98-6
BUTANE	C <sub>4</sub> H <sub>10</sub>	30-60%	109-97-8

### 4. FIRST AID MEASURES

<b>Eye</b>	Hold eyelids apart and flush continuously with water. Continue until advised to stop by the Poisons Information Centre, a doctor, or for at least 15 minutes. Keep patient calm.
<b>Inhalation</b>	Leave area of exposure immediately. If irritation persists, seek medical attention.
<b>Skin</b>	Gently flush affected areas with water. Seek medical attention, if irritation persists.
<b>Ingestion</b>	For advice, contact a Poisons Information Centre on 0800 764 766 (0800 POISON) or +64 9 579 5139 (New Zealand) or a doctor. If swallowed, DO NOT induce vomiting, as ingestion is considered unlikely, due to the product form.
<b>Advice to Doctor</b>	Treat symptomatically.
<b>First Aid Facilities</b>	Eye wash facilities should be provided.

### 5. FIRE FIGHTING MEASURES

<b>Flammability</b>	Highly flammable. Vapours may form explosive mixtures with air. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition temperatures. When handling a significant spillage, eliminate all ignition sources, including cigarettes, open flames, spark producing switches, heaters, naked lights, mobile phones, etc. Aerosol cans may explode when heated above 50 °C.
<b>Fire and Explosion</b>	Highly flammable, explosive vapour. Evacuate area and contact emergency services. Toxic gases may evolve, when heated. Remain upwind and notify those downwind of hazard. Wear full protective equipment, including Self Contained Breathing Apparatus (SCBA), when combating fire.

---



---

Use waterfog to cool intact containers and nearby storage areas.

**Extinguishing** Dry agent, carbon dioxide foam, or water fog. Prevent contamination of drains or waterways; absorb runoff with sand or similar. Do not use water jet as this may spread fire.

**HazChem** 2Y

## 6. ACCIDENTAL RELEASE MEASURES

**Spillage** If large quantities of cans are punctured (bulk), clear area of all unprotected personnel and ventilate area. Wear splash-proof goggles, leather gloves, coveralls, and boots. Where inhalation risks exist, wear a Type A-Class P1 (Organic vapour and Particulate) respirator. Remove all sources of ignition. Collect cans and allow to discharge outdoors. Absorb any residues with sand or similar and place in clean containers for disposal. DO NOT wash away into sewer.

## 7. HANDLING AND STORAGE

**Handling** Use safe work practices to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Keep out of the reach of children. Do not use if pregnant. Void prolonged exposure.  
DO NOT puncture aerosol cans or incinerate, even when empty.  
DO NOT cut, weld, solder drill, grind or smoke whilst using. Use caution around energised equipment

**Storage** Store in a cool, dry well-ventilated area, well away from oxidising agents, acids, alkalis, direct sunlight, heat or ignition sources, or foodstuffs. Ensure containers are adequately labelled, protected from physical damage, and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate fire protection.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Ventilation** DO NOT directly inhale concentrated vapours. Use in well-ventilated areas. Mechanical extraction ventilation is recommended for poorly ventilated area. Vapours are heavier than air and may travel some distance to an ignition source and flash back. Maintain vapour levels below the recommended exposure standard.

**Exposure Standards** LIQUIFIED PETROLEUM GAS (LPG) (68476-85-7)  
ES-STEL: 400 ppm (1800 mg/m<sup>3</sup>)

**Personal Protection Equipment** No personal protective equipment is required, normally. When an inhalation risk exists wear a Type A-Class P1 (Organic vapour and Particulate) Respirator. With prolonged use, wear PVC or rubber gloves and splash-proof goggles or safety glasses.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	COLOURLESS AEROSOL	<b>Solubility (water)</b>	DISPERSABLE
<b>Odour</b>	SWEET ODOUR	<b>Specific Gravity</b>	0.80 - 0.82
<b>pH</b>	NOT AVAILABLE	<b>% Volatiles</b>	100 %
<b>Vapour Pressure</b>	6962Pha estimated	<b>Flammability</b>	HIGHLY FLAMMABLE
<b>Vapour Density</b>	> 1 (Air = 1)	<b>Flash Point</b>	< 20 °C (Propellant)
<b>Melting Point</b>	NOT AVAILABLE	<b>Upper Explosion Limit</b>	12.8% ESTIMATED
<b>Boiling Point</b>	NOT AVAILABLE	<b>Lower Explosion Limit</b>	1.2% ESTIMATED
<b>Evaporation Rate</b>	FAST	<b>Auto-ignition Temperature</b>	NOT AVAILABLE

## 10. STABILITY AND REACTIVITY

<b>Reactivity</b>	This product is stable and non-reactive under normal conditions of use, storage and transport
<b>Chemical Stability</b>	This product is stable under normal conditions
<b>Decomposition Products</b>	May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition temperatures.
<b>Conditions to Avoid</b>	Heat, flames and sparks.
<b>Incompatible Materials</b>	Acids, Aluminium

## 11. TOXICOLOGICAL INFORMATION

<b>Health Hazard Summary</b>	<p>General population. The exposure of the general population is expected to be low and is not likely to present a hazard when it is used as recommended.</p> <p>Occupational exposure. With reasonable work practices, hygiene measures and Safety precautions is unlikely to be an occupational hazard.</p> <p>Asphyxiant narcotic. This product may only present a hazard with direct eye contact, prolonged and repeated skin contact or with vapour/gas inhalation at high levels.</p>
------------------------------	---



<b>Eye</b>	Causes serious eye irritation
<b>Inhalation</b>	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness, headache, nausea, vomiting.
<b>Skin</b>	Low irritant. Prolonged contact may result in irritation, redness, rash, dermatitis, and sensitisation.
<b>Ingestion</b>	May result in liver and kidney damage

## 12. ECOLOGICAL INFORMATION

<b>Environment</b>	Environmental effects of the compound are extremely unlikely, due to packaging in the form of an aerosol. Ensure appropriate measures are taken to prevent this product from entering the environment through wastewater. Acute to Fish species
--------------------	--

## 13. DISPOSAL CONSIDERATIONS

<b>Waste Disposal</b>	For small amounts, absorb contents with sand or similar and dispose of to an approved landfill site. DO NOT puncture or incinerate aerosol cans. Contact the manufacturer for additional information.  Contents under pressure do not crush, incinerate or puncture. Do not allow this material to drain into sewers/water supplies.
<b>Hazardous Waste</b>	D001: Waste Flammable material with flashpoint ,140F
<b>Legislation</b>	Dispose of in accordance with relevant, local legislation.

## 14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG AND HZNO CODES.

	Shipping Name	UN No	Packing Group	DG Class	Subsidiary Risk(s)	EPG
<b>Land</b>	Compressed Gas Flammable Aerosol	1950	None Allocated	2.1	None Allocated	2C1
<b>Sea</b>	Compressed Gas Flammable Aerosol	1950	III	2.1	None Allocated	2C1

Shipping Label



## 15. REGULATORY INFORMATION

**Poison Schedule** A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).  
**AICS** All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

## 16. OTHER INFORMATION

**Additional Information** ASPHYXIANTS (1): reduce the oxygen concentration by displacement, when present in the atmospheres, in high concentrations. As most simple asphyxiants are odourless, atmospheres deficient in oxygen do not provide adequate sensory warning of danger. Therefore, it is not generally appropriate to recommend an exposure standard for each asphyxiant, but instead warn of the need to maintain oxygen concentrations.

Some asphyxiants may be given an exposure standard, due to their potential for narcotic effects at high concentrations, or an explosion hazard.

**Asphyxiants (2)** There is a significant hazard associated with workers entering poorly, ventilated areas (e.g. tanks) where oxygen levels may be deficient. An air supplied breathing apparatus may be required if adequate ventilation is not ensured. Refer to AS/NZS 2865 - Safe Working in a Confined Space.

**Respirators** In general, the best practice to avoid exposure is to use engineering controls, such as adequate ventilation, rather than the use of respirators (which should be limited).  
If respiratory equipment must be worn, ensure correct respirator selection and training is undertaken. Some respirators may be extremely uncomfortable, when used for long periods. The use of air powered, or air supplied respirators should be considered where prolonged or repeated use is necessary.

**Abbreviations** Mg/m<sup>3</sup> - Milligrams per cubic metre  
ppm - Parts Per Million  
M - moles per litre, a unit of measure of concentration.  
pH - relates to hydrogen ion concentration - this value will relate to a scale of 0 – 14, where 0 is highly acidic and 14 is highly alkaline.  
TWA/ES - Time Weighted Average or Exposure Standard.  
CAS# - Chemical Abstract Service number - uniquely identifies chemical compounds.  
CNS - Central Nervous System  
NOS - Not Otherwise Specified  
IARC - International Agency for Research on Cancer.

**Personal Protective** The recommendations for protective equipment contained within this SDS report are provided as a guide only, when dealing with an abnormal situation. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering



---

<b>Equipment</b>	controls should be considered, before the final selection of personal protective equipment is made.
<b>Health Effects from Exposure</b>	It should be noted that the effects from excess exposure to this product would depend on several factors, including duration of exposure, quantity involved, effectiveness of control measures used; protective equipment and method of application. Given that, it is impractical to prepare an SDS report, which would encompass all possible scenarios, it is anticipated that users will assess the risks in an emergency and apply appropriate control methods.
<b>Report Status</b>	This report is based upon information provided by ingredient manufacturers, and third-party experts. We believe that the information represents the current state of knowledge about safety and handling precautions that are appropriate for this product. Further clarification regarding any aspect of the product should be obtained directly from the Chief Chemist at Arandee Ltd. While Arandee has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy, or completeness. As far as lawfully possible, Arandee accepts no liability for any loss, injury, or damage (including consequential loss) which may be suffered, or incurred by any person, because of their reliance upon the information contained in this Safety Data Sheet.